



QUALITY ★★★★★



Powerstation 909

High-end multiple plug socket

OEHLBACH's Powerstation 909 is a perfectly made multiple plug socket designed as a 19" rack / table version that will satisfy even the highest of demands made at the top end of the segment. It possesses a total of eight individual sockets – four digital (filtered) and four analogue (unfiltered) plug sockets. Also, two separate plug-socket groups consisting of two filtered and unfiltered plug sockets each may be switched individually. The Powerstation 909 possesses phase marks at each individual plug socket and the correct connections are indicated by a red control lamp in order to ensure that the equipment's phases are properly connected. This is the only way to effectively prevent potential-equalization currents from interfering with audio and image data. This exceptional plug socket has also been equipped with a delay function (three seconds) for the mains switch to prevent unpleasant current peaks when it is switched on. The display which may be switched off and which has been embedded in the solid aluminium front panel provides users with information about power consumption and the voltage at the time. The inner conductor's cross-section of 3.3 mm², which has been made from highly pure oxygen-free copper, constitutes genuine high-end inner cabling and will guarantee stable power supplies in any situation – even for components with high power requirements.



Special aspects

If the surge protection function of the Powerstation 909 is triggered as a result of extreme voltage peaks, the eight sockets are disconnected from the mains. The Powersocket can be used again by pressing the RESET button. Correct operation of the active surge protection function is indicated by the PROTECTED light.



Designation	Art. No.	Unit	Colour
Powerstation 909	13050	1 Pc.	black

Features

- ✓ 8 individual plug slots
- ✓ 4 unfiltered plug sockets
- ✓ delay function for main switch
- ✓ Solid aluminium front panel
- ✓ Sheath current filter to prevent ground loops
- ✓ 24 ct gold plated plug
- ✓ OFC – oxygene free copper
- ✓ Reliable contact
- ✓ switchable display
- ✓ RFI mains switch from studio engineering
- ✓ Inner conductors made from oxygen-free copper
- ✓ Overvoltage protection with LED
- ✓ Phase-correct connection through LED
- ✓ incl. main switch

Technical Data

Power supply	Mains voltage: 230V / 50Hz
Dimensions	909

24 ct

100% Contact