







The driving spirit behind Vivid Audio is the continuous quest for perfection, so any hint that an improvement is possible has to be pursued and tested.

Welcome to the G1 Spirit

GIYA G1 SPIRIT Welcome to the continuous quest for perfection.

It has been said that improving the G1 would be like gilding a lily, there's no question that the bar has been set very high. Nevertheless, the driving spirit behind Vivid Audio is that any hint that an improvement is possible has to be pursued, tested and perfected.

When reviewing improvements it resulted in the opportunity to reconsider multiple aspects of the design. Including a new aspect to the exterior shell with longer wider port for increased linear LF output, new C225-100 bass drivers, Lower-mid driver C125-75 with carbon rings, chassis and CNC machined sandwich composite stiffening braces.

Specification

Configuration Cabinet material Cabinet colour Bespoke cabinet colour Drive units

Bass loading Sensitivity Nominal impedance (Ω) Frequency range (Hz) First D26 Break Up mode: Frequency response Harmonic distortion (2nd and 3rd harmonics) Cross over frequencies (Hz) Power handling (music program) watts rms Loudspeaker dimensions Net weight 4-way 5-driver system Glass reinforced balsa cored sandwich composite Piano, Pearl Bespoke colour options available on request HF: D26—26mm metal dome unit with Tapered Tube loading Mid: D50 — 50mm metal dome unit with Tapered Tube loading Lower-mid: C125-75s, 125mm alloy/carbon diaphragm with 75mm voice coil Bass: 2 x C225-100, 225mm alloy diaphragm with 100mm voice coil in 45mm gap Exponentially tapered tube enhanced bass reflex 92dB @ 2.83VRMS at 1m on axis 6 nominal, 3 minimum at 20KHZ no phase shift at Zmin - 6dB points: 25-36,000 Hz 44,000 Hz 29-33,000Hz +/- 2dB on reference < 0.3% over frequency range 220, 880, 3500

GIYA G1 SPIRIT



For more details about the GIYA G1s or accessories to compliment, please consult your local specialist retailer, or visit www.vividaudio.com



Head office & Showroom: Vivid Audio, 6 Star Road, Partridge Green, West Sussex, RH13 8RA, UK Tel: +44 (0) 1403 713125 Email: info@vividaudio.com

1600

1600mm (H) x 440mm (W) x 820mm (D)

80kg (86kg with cross over)









V1s (stand)

V1w (wall mounted)